

**NORTHERN GREECE CERAMICS S.A.**

Nea Santa 61100 - Kilkis, Greece

Tel: 0030 23410 75570

Fax: 0030 23410 75574

Email: info@kebe-sa.gr

web: www.kebe-sa.gr

EST. 1935

KOTHALI**KEBE**

NORTHERN GREECE CERAMICS

12**EN 771-1:2011+A1:2015****B250-12/33****Horizontally Perforated Clay Masonry unit P, for use in protected masonry,
Category II**

DOP Reference No	B250-12/33-25	
Length	330	mm
Width	250	mm
Height	120	mm
Dimensional tolerance	T1	
Range category	R1	
Flatness of bed faces	≤ 2	mm
Plane parallelism of bed faces	≤ 2	mm
Configuration	As in attached drawing	
Gross dry density	755	kg/m ³
Net dry density	1.910	kg/m ³
Density tolerance	D1:10	%
Mean compressive strength (perpendicular to bed face)	≥3,0	N/mm ²
Category	II	
Bond strength (Tabulated value acc.to EN 998-2 Annex C)	0,15	N/mm ²
Thermal conductivity λ _{eq}	NPD	
Water vapour permeability μ	5/10	
Durability against freeze/thaw	F0	
Water absorption	≤ 14	%
Active soluble salt content	S0	
Reaction to fire : Euroclass	A1	
Dangerous substances	NPD	

Particular conditions applicable to the use: Cutting with power tools may generate dust. This dust will contain silica or quartz particulate which may constitute a hazard. People undertaking works of this nature are advised to wear dust masks FFP3 (EN 149).

