

**NORTHERN GREECE CERAMICS S.A.**

Nea Santa 61100 - Kilkis, Greece

Tel: 0030 23410 75570

Fax: 0030 23410 75574

Email: info@kebe-sa.gr

web: www.kebe-sa.gr

EST. 1935

KOTHALI**KEBE**

NORTHERN GREECE CERAMICS

12**EN 771-1:2011+A1:2015****Λ No 180****Horizontally Perforated Clay Masonry unit P, for use in protected masonry,
Category II**

DOP Reference No	AN180-25		
Length	330	330	mm
Width	180	140	mm
Height	140	180	mm
Dimensional tolerance	T1		
Range category	R1		
Flatness of bed faces	NPD		
Plane parallelism of bed faces	NPD		
Configuration	As in attached drawing		
Gross dry density	600		kg/m ³
Net dry density	1.550		kg/m ³
Density tolerance	D1:10		%
Mean compressive strength (perpendicular to bed face)	≥3,0		N/mm ²
Category	II		
Bond strength (Tabulated value acc.to EN 998-2 Annex C)	0,15		N/mm ²
Thermal conductivity λ _{10,dry,unit} (P3)	NPD		
Water vapour permeability μ	5/10		
Durability against freeze/thaw	F0		
Water absorption	NPD		
Active soluble salt content	S0		
Reaction to fire : Euroclass	A1		
Dangerous substances	NPD		

Particular conditions applicable to the use:

Cutting with power tools may generate dust. People undertaking works of this nature are advised to wear suitable personal protective equipment (PPE)

